



IMPORTANT: SEE DRAWING D-600-0055 FOR FRAMING REQUIREMENTS

**TNR INDUSTRIAL DOORS INC.**

**SHOP DRAWING, MODEL HDXL 9, LEFT HAND**

EXT. DETAIL: DOOR MT. OPERATOR & C/BAL SPRINGS, 2 PC. IDLER

LIMITATIONS: (35' 0" < OW <= 50' 0") & (OH <= 25' 0")

DATE DR'N: JAN. 07, 2010

REVISION: RELEASE

DRAWN BY: R.B.

DRAWING No.: D-600-0053

ELECTRICAL CRITERIA:

CONTROL PANEL NEMA/EEMAC 4 STD. OR \_\_\_\_\_

PRIMARY POWER SUPPLY: \_\_\_\_\_ Volts, 3 Phase, 60 Hertz

OPERATOR CRITERIA: HG, HIGH EFFICIENCY HELICAL GEAR

LIMIT BOX NEMA/EEMAC 4 STD. OR \_\_\_\_\_

\_\_\_\_\_ HP, DOOR SPEED: OPEN & CLOSE @ \_\_\_\_\_ ips

END USER:

DEALER:

DOOR SIZE:

SERIAL No.:

MECHANICAL OPTIONS	ELECTRICAL OPTIONS	STANDARD SYSTEM INCLUDES
<input type="checkbox"/> - *** GALV. DOOR HOODS	<input type="checkbox"/> - RELAY LOGIC CONTROLS	- SPEED AS SHOWN
<input type="checkbox"/> - 16" x 16" WINDOWS, QTY. _____	<input type="checkbox"/> - FUSED DISCONNECT	- NEMA 4, WALL MOUNTED CONTROL PANEL
<input type="checkbox"/> - BLUE EPDM CURTAIN	<input type="checkbox"/> - LOOP DETECTOR	- NEMA 4 LIMIT BOX ON OPERATOR
<input type="checkbox"/> - GRAY EPDM CURTAIN	<input type="checkbox"/> - WIRELESS RECEIVER (OCS)	- 50,000 CYCLE COUNTERBALANCE SPRINGS
<input type="checkbox"/> -	<input type="checkbox"/> - WIRELESS TRANSMITTER (OCS), QTY. _____	- REVERSING EDGE
<input type="checkbox"/> -	<input type="checkbox"/> - N 4X, PUSHBUTTON ST'N, QTY. _____	- THRU-BEAM PHOTOEYE
<input type="checkbox"/> -	<input type="checkbox"/> - MOTION DETECTOR, QTY. _____	- 5" HIGH, BLACK EPDM RUBBER LOOP
<input type="checkbox"/> -	<input type="checkbox"/> - ADD. THRU-BEAM PHOTOEYE, QTY. _____	- NEWGEN II GUIDE AND CURTAIN LOK SYSTEM
<input type="checkbox"/> -	<input type="checkbox"/> - ADD. REFLECTIVE PHOTOEYE, QTY. _____	- PROGRAMMABLE CONTROLLER
<input type="checkbox"/> -	<input type="checkbox"/> - CONSTANT PRESSURE CLOSE	- GUIDE GUARDS - 8 FT HIGH
<input type="checkbox"/> -	<input type="checkbox"/> -	- STATIONARY WINDBAR
<input type="checkbox"/> -	<input type="checkbox"/> -	-